

Product: M25158 - Cruz Marine Vinyl Upholstery

S.No.	Tests		Method	Specification
1	Total Weight (G/m ²)		ASTM D-751	620 +/-10%
2	Thickness (mm)			1.00 +/- .10
3	Tensile Strength (kg) grab method	Warp	ASTM D-751	36 MIN
		Weft		32 MIN
4	Tear Strength (Kgf) tongue method	Warp	ASTM D-751	2.7 MIN
		Weft		2.7 MIN
5	Ply Adhesion (Kg/5cm)	Warp	ASTM D-751	2.5 MIN
		Weft		2.5 MIN
6	Elongtion at Break (%)	Warp	ASTM D-751	50 MIN
		Weft		190 MIN
7	Flame Resistance		FMVSS 302, CAL 117 Section E, BS 5852 (Crib0, 1)	PASS
8	Cold Resistance		ASTM 191-5874	PASS
9	Abrasion	Martindale	100000 CYCLE	PASS
		Wyzenbeek (10 cotton duck)	50000CYCLE (ASTM D-4157)	PASS
10	UV Resistance		QUV-B (5000hrs)	PASS
11	Mildew Resistance		CFFA-120 (ASTM G21-09)	PASS
12	Antimicrobial/ Antibacterial		CFFA-300 (AATC 147-2004)	PASS
13	Roll length			30 m
14	Width			140 cm